



Isetta LX/ST Gelato

4 • 6R • 7R • 9R • 12R

Gelato cabinets with static refrigeration. One piece body with ecological polyurethane insulation [HCFC & HFC free], foamed with CO2. Tempered glass structure. Internal and external tank in plastified sheet. This cabinet can be fitted with a double level of ice-cream containers 4 23/32h.

| (| REFRIGERANT | R404A |
|----------|---------------------|----------------------|
| ∞ | ENERGY SAVING | Led |
| 4 | INSTALLATION | Plug-In |
| | PROCUCT TEMPERATURE | 3,2 / 6,8 °F |
| | DEFROST | Electric |
| | CLIMATIC CLASS | 7 (95 °F / 75% R.H.) |
| 滐 | REFRIGERATION | Static |
| | CLOSING SYSTEM | Tilting panel |

STANDARD MODEL INCLUDES:

- \bullet Operator side closure with pivoting methacrilate panel system
- Work top in plastified sheet
- Refrigerated storage cell (6R-7R-9R-12R models only)
- Electronic control panel
- Swivel casters with brake
- Led lighting



Piled up double row 5 It [Large] 14 3/16 x 6 1/2 x 4 23/32h



Refrigerated storage cell 6R - 7R - 9R - 12R











Isetta LX/ST Gelato





NOTE: The model does not included stainless steel containers.

| TECHNICAL FEATURES | 3 | | 4 | 6R | 7R | 9R | 12R |
|---------------------|-------------|--------|---------------------------|--------|---------|---------|---------|
| External dimensions | Lenght | inch | 32 7/16 | 46 5/8 | 53 5/16 | 65 5/16 | 83 7/16 |
| Capacity | Gross / Net | liters | - | - | - | - | - |
| Weight | Net | lb | 152 | 214 | 225 | 353 | 478 |
| Refrigerant | | | R404A | | | | |
| Product temperature | | °F | 3.2 / 6.8 | | | | |
| Compressor | Type / Q.ty | | Hermetic / 1 Hermetic / 2 | | | | |
| Defrost | •••••• | | Flectrical | | | | |

| STAINLESS STEEL CONTAINERS | | 4 | 6R | 7R | 9R | 12R |
|----------------------------|----------------------------|---------|---------|---------|---------|-----------|
| 4,75 lt (Standard) | 10 1/4 x 6 3/16 x 6 11/16H | 6 | 10 | 11 | 14 | 19 |
| 5 lt (Large) | 14 3/16 x 6 1/2 x 4 3/4H | 4 + [4] | 6 + [6] | 7 + [7] | 9 + [9] | 12 + [12] |

| ELECTRICAL DATA | 12 | 16 | 18 | 20 | 12+12 |
|--------------------|------------------------------------|-----|-----|--------------------------------------|-------|
| Power supply | 115 / 60 2 pole - 3 wire grounding | | | 220 / 60 / 2 pole - 3 wire grounding | |
| Nema plug | 5-15P 6-15F | | | 15P | |
| Electrical input A | 8,2 | 9,2 | 9,2 | 7 | 7,7 |

Technical info refers to models with built-in air cooled condensing unit.

| PACKAGING STANDARD (Wooden crate) | | | 4 | 6R | 7R | 9R | 12R |
|-----------------------------------|----------------|------|--------------------|---------|----------|----------|----------|
| External dimensions | Lenght | inch | 37 13/32 | 51 3/16 | 55 29/32 | 69 11/16 | 88 19/32 |
| | Depth x Height | inch | 35 7/16 x 45 21/32 | | | | |
| Gross weight | | lb | 209 | 264 | 286 | 352 | 485 |









Carpigiani North America ISA S.p.A.

3760 Industrial Drive Winston-Salem NC 27105

www.carpigiani-usa.com

Via Madonna di campagna, 123 06083 Bastia Umbra (PG) Italy

T. +39 075 801 71

F. +39 075 800 09 00

E. customerservice@isaitaly.com

www.isaitaly.com